



SAH-120

Mesothermal Type Antifoam

PDS

Description

SAH-120 is a water-dilutable antifoam that is designed to control foam in aqueous systems. It can use in a wide range of aqueous system applications.

Storage & packaging

When stored in its originally sealed packaging at 5°C - 40°C, this product may be stored for up to 8 months from its manufacturing date. Comply with the storage instructions marked on the packaging. Once past this expiration date, TAI COUNTY CHEMICAL no longer guarantees that the product meets the sales specifications. Product comes in 120 kg drums.

Characteristics

- Good resistance to alkalis and acids
- Compatible with most silicone emulsions if blending is required
- Excellent compatibility with water
- A small volume of usage
- Fast defoaming ability

Applications

- Remove foam in various processes and waste water treatments
- Control foams formed from acrylic resins or water jet loom sizing agent stirring processes
- Suppress the foam of surfactants (foam free detergent, dispersing agent, scouring agent, etc.)
- Foam suppression for rubber latex gloves and rubber industries

Properties

Appearance	Milky yellowish liquid
Active ingredient(%)	30.0%
pH(10%Solution,25°C)	7.5±1.0
Ionic type	Nonionic
Diluent	Water

Processing

- Usage amount is 0.1~0.3%.
- (Depending on the actual conditions, you can adjust the usage amount.)

Safety

This document does not contain the safety information required for the product. Please read the safety data sheet for this product before use.

The data provided above is to the best of our knowledge and experience and is without any warranty. Users should thoroughly test any application and independently conclude satisfactory performance before use.

TAI COUNTY CHEMICAL

www.taicounty.com.tw
 No. 91, Museum Rd., Bali DIST., NEW
 TAIPEI CITY 24947, TAIWAN
 Tel: 886-2-2610-4457
 Fax: 886-2-2610-1363
 E-MAIL : service@taicounty.com.tw
 FACTORY REGISTRATION NO:
 99.695614.00