



SAS-120

Ordinary Temperature Type Antifoam

**PDS** 

## **Description**

SAS-120 Antifoam is a water-dilutable, low viscosity silicone emulsion that is designed to control foam in aqueous systems. It has excellent resistance to acids and alkalis and can use for a broad range of applications in aqueous systems.

#### **Characteristics**

- Excellent resistance to alkalis and acids
- · Prolong defoaming performances
- · Cost-effective (A small volume of usage)
- SAS-120 Does do not react with other substances in the bath
- Compatible with most silicone emulsions if blending desired

## **Properties**

Appearance	Milky yellowish liquid
Active ingredient(%)	30.0%
pH(10%Solution,25°C)	7.5 <b>±</b> 1.0
Ionic type	Nonionic
Diluent	Water

#### Safety

This document does not contain the safety information required for the product. Please read the safety data sheet for this product before use.

# Storage & packaging

When stored in its originally sealed packaging at 5°C - 40°C, this product may be stored for up to 8 months from its manufacturing date. Comply with the storage instructions marked on the packaging. Once past this expiration date, TAI COUNTY CHEMICAL no longer guarantees that the product meets the sales specifications. Product comes in 120 kg drums.

## **Applications**

- Combats foam generated in surfactant containing formulations
- Ideal for controlling foams in textile auxiliaries
- Controls foam in various processes and waste water treatments
- Foam control for latex paint or printed circuit boards

### **Processing**

 To dilute to 10% emulsion (Filter before packaging)

Total	:120.5KG
Water	:80 KG
CB-3(Thickener)	:0.4 KG
ANTK(Antiseptic)	:0.1 KG
SAS-120	:40 KG

- Amount required for liquid formulations may differ, depending on the desired degree of foam control.
- Recommended usage is usually between 0.1 and 0.3%

(Depending on the actual conditions, you can adjust the usage amount.)

The data provided above is to the best of our knowledge and experience and is without any warranty. Users should thoroughly test any application and independently conclude satisfactory performance before use.

# TAI COUNTY CHEMICAL

TAIPEI Factory: NO. 91, Museum Rd., Bali Township, Taipei County 24947, Taiwan FACTORY REGISTRATION NO: 99.695614.00

YUNLIN Factory: NO. 1, Changqing St., Lunbei Township, Yunlin County 63745, Taiwan FACTORY REGISTRATION NO: 09000892

Tel: 886-2-2610-4457

Fax: 886-2-2610-1363

E-MAIL: service@taicounty.com.tw

www.taicounty.com.tw